



## Technical data

Substance		
Fleece	special fleece made of PP	
Adhesive	special acrylate adhesive	
Release film	silicone-coated PE film	
Attribute	Regulation	Value
Colour		light blue
Thickness		0.5 mm
Exposure time		3 months
Can be plastered over		yes
Application temperature		above -10 °C / 14 °F
Temperature resistance		permanent -40 °C/-40 °F to +90 °C/194 °F
Storage		cool and dry

## Area of application

Pre-folded corner tap to stick

- ✓ Vapour retarding and airproofing layers consisting of membranes and wood-based panels (e.g. OSB) one below the other
- ✓ Roof lining, sarking and wall lining membranes one below the other
- ✓ Connections to adjacent structural elements such as windows, doors etc. internally and externally.

The bonds meet the requirements of DIN 4108-7, SIA 180 and OENORM B 8110-2.

## Advantages

- ✓ Simple, quick and clean corner sealing as a result of pre-folding
- ✓ No release paper on the first adhesive side: stick down the tape immediately, no need to remove and dispose of the first backing strip
- ✓ Available in strip widths of 25/35 mm and 12/38 mm
- ✓ Soft fleece backing
- ✓ Moisture-resistant adhesive for permanently secure internal and external sealing
- ✓ Can be plastered over

## Substrates

Before bonding, the substrate surface should be swept clean with a broom or wiped with a cloth.

Bonding to frozen surfaces is not possible. The substrate material must be free of water-repellent substances (e.g. grease or silicone). Substrates must offer sufficient load-bearing capacity.

Permanent adhesion to all pro clima membranes (vapour-retarding and airtightness membranes, trickle protection membranes and roof lining, sarking and wall lining membranes) and PE, PA, PP aluminium films for creating airtightness or windtightness.

Bonding is also possible with planed and painted wood, high density plastic and metal (e.g. pipes, windows etc.), hardboard (chipboard, OSB and veneer plywood, MDF board and softwood fibre sub-roof panels).

Pre-treat wood fibre sub-roof panels with TESCO PRIMER RP. Concrete or plaster subsurfaces must not be sandy or crumbling.

The best results for the safety of the structure can be achieved on high-quality substrates.

You are responsible for checking the suitability of the substrate.

Adhesion tests are recommended.

## General conditions

The bonds should not be subjected to tensile strain.

After sealing the vapour retarding membranes, the weight of the insulating material must be borne by lathing.

The adhesive tape should be supported by battens if necessary.

Press firmly to secure the adhesive tapes, taking care to ensure that there is sufficient resistance pressure behind them.

Windproof, airtight or rainproof seals can only be achieved on vapour retarding membranes, roof lining membranes or façade membranes that have been laid without folds or creases.

Ventilate continuously and systematically to prevent build-up of excessive humidity; use a dryer if necessary.

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about the application and construction can be found in the pro clima planning documentation. For queries please call the pro clima technical hotline on +49 (0)6202 278245.

### MOLL

bauökologische Produkte GmbH

Rheintalstraße 35 - 43

D-68723 Schwetzingen

Fon: +49 (0) 62 02 - 27 82.0

Fax: +49 (0) 62 02 - 27 82.21

eMail: info@proclima.de



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about the application and construction can be found in the pro clima planning documentation. For queries please call the pro clima technical hotline on +49 (0)6202 278245.

**MOLL**  
**bauökologische Produkte GmbH**  
Rheintalstraße 35 - 43  
D-68723 Schwetzingen  
Fon: +49 (0) 62 02 - 27 82.0  
Fax: +49 (0) 62 02 - 27 82.21  
eMail: [info@proclima.de](mailto:info@proclima.de)

