



### Technical Data:

Characteristics	Value
material	UNI TAPE with EPDM
temperature resistance EPDM	long term -40°C to +120°C
application temperature	from -10°C
colour	blue / black
storage	cool and dry

### Applications:

Sealing grommet made of strong and highly flexible EPDM. Ideally suited for rapid and permanent airtight feed-throughs for cables and pipes through the airtight sealing layer. Can also be used outdoors, e.g. for sub-roofs and for refurbishment vapour check by sticking waterproof TESCON No.1 or TESCON VANA adhesive tape over the light blue paper backing on the self-adhesive grommets.

### Delivery Form:

Mat. No.	EAN	Length	Width	PU	
10730	4026639016393	14.5 cm	14.5 cm	5	ROFLEX 20 for pipes Ø 15-30 mm
10731	4026639016416	14.5 cm	14.5 cm	30	ROFLEX 20 for pipes Ø 15-30 mm

### Surfaces:

Before bonding, the substrate surface should be swept clean with a broom or wiped with a cloth. Bonding to frozen surfaces is not possible. The substrate material must be free of water-repellent substances (e.g. grease or silicone). The substrate must offer sufficient load-bearing capacity.

A permanent bond is achieved on all pro clima indoor and outdoor membranes (vapour check and airtightness membrane as well as trickle protection membrane and sarking membrane or wall lining membrane) and PE, PA, PP, aluminium foil used to create an airtight seal. Bonding and joints are possible on planed and painted wood, high density plastic and metal (e.g. pipes, windows etc.), hardboard (chipboard, OSB and veneer plywood, MDF board and softwood fibre sub-roof panels). Softwood fibre sub-roof panels require pre-treatment with TESCON PRIMER RP before bonding. For outdoor use, stick TESCON No.1 or TESCON VANA over the UNI TAPE.

The best results for the safety of the structure can be achieved on high-quality substrates. The applicator is responsible for checking the suitability of the substrate. Adhesion tests are recommended.

### Features/advantages:

Made of high-quality EPDM, ideal for permanently airtight cable and pipe penetrations. Quick installation. The cables and pipes can be still be pulled or pushed without damaging the airtightness.

- ✓ Secure bond, quick and secure sealing
- ✓ Extremely flexible and elastic
- ✓ Need, efficient and quick installation
- ✓ Also suitable for penetrations under the roof

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommendations given or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and UK:  
Phone: +353 46 9432104  
Fax: +353 46 9432435  
[info@ecologicalbuildingsystems.com](mailto:info@ecologicalbuildingsystems.com)

For Stockists contact  
Ireland  
T. 046 9432104  
F. 046 9432435  
UK  
T. 05600 758025  
F. 05600 758026

Ecological Building Systems Ltd.

[info@ecologicalbuildingsystems.com](mailto:info@ecologicalbuildingsystems.com)  
[www.ecologicalbuildingsystems.com](http://www.ecologicalbuildingsystems.com)

