

ROFLEX 50-200

Sealing grommets for pipes



Technical Data:

Characteristics	Valeur
material	EPDM
temperature resistance EPDM	long term -40°C to +120°C
application temperature	from -10°C
colour	black

Applications:

Sealing grommet made of strong and highly flexible EPDM. Ideally suited for rapid and permanent airtight feed-throughs for cables and pipes through the airtight sealing layer. Can also be used outdoors, e.g. for sub-roofs and for refurbishment vapour check. Stick with TESCON No.1 or TESCON VANA.

Delivery Form:

Mat. No.	EAN	Length	Width	UE	
10732	4026639016430	14 cm	14 cm	2	ROFLEX 50 for pipes Ø 50-90 mm
10733	4026639016447	14 cm	14 cm	20	ROFLEX 50 for pipes Ø 50-90 mm
10734	4026639016454	20 cm	20 cm	2	ROFLEX 100 for pipes Ø 100-120 mm
10735	4026639016461	20 cm	20 cm	20	ROFLEX 100 for pipes Ø 100-120 mm
10736	4026639016478	25 cm	25 cm	2	ROFLEX 150 for pipes Ø 120-170 mm
10737	4026639016485	25 cm	25 cm	20	ROFLEX 150 for pipes Ø 120-170 mm
10738	4026639016492	30 cm	30 cm	2	ROFLEX 200 for pipes Ø 170-220 mm
10740	4026639016508	30 cm	30 cm	20	ROFLEX 200 for pipes Ø 170-220 mm

Surfaces:

Before bonding, the substrate surface should be swept clean with a broom or wiped with a cloth. Bonding to frozen surfaces is not possible. The substrate material must be free of water-repellent substances (e.g. grease or silicone). The substrate must offer sufficient load-bearing capacity.

A permanent bond can be achieved with the adhesive tapes specified on all pro clima indoor and outdoor membranes (vapour check and airtightness membrane as well as trickle protection membrane and sarking membrane or wall lining membrane) and PE, PA, PP, aluminium foil used to create an airtight seal. Bonding and joints are possible with planed and painted wood, high density plastic and metal (e.g. pipes, windows etc.), hardboard (chipboard, OSB and veneer plywood, MDF board and softwood fibre sub-roof panels). Softwood fibre sub-roof panels require pre-treatment with TESCON PRIMER RP before bonding.

The best results for the safety of the structure can be achieved on high-quality substrates. The applicator is responsible for checking the suitability of the substrate. Adhesion tests are recommended.

Features/advantages:

Made of high-quality EPDM, ideal for permanently airtight cable and pipe penetrations. Quick installation. The cables and pipes can be still be pulled or pushed without damaging the airtightness.

- ✓ Secure bond, quick and secure sealing
- ✓ Extremely flexible and elastic
- ✓ Need, efficient and quick installation
- ✓ Also suitable for penetrations under the roof

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommendations given or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and UK:
Phone: +353 46 9432104
Fax: +353 46 9432435
info@ecologicalbuildingsystems.com

For Stockists contact
Ireland
T. 046 9432104
F. 046 9432435
UK
T. 05600 758025
F. 05600 758026

Ecological Building Systems Ltd.

info@ecologicalbuildingsystems.com
www.ecologicalbuildingsystems.com

