

TESCON PRIMER RP

Solvent-free primer,
no drying required

NEW



iab
Bord Agrément no 16/1999
Irish Agrément Board

Technical Data:

Characteristics	Value
material	acrylic copolymer, solvent-free
temperature resistance	-40°C to +90°C
application temperature	-10°C to +45°C
storage	cool and dry, protect from frost

Applications:

Adhesive primer for wood, fibreboard, masonry, roof, wall and floor boards for preparing or priming the substrate for subsequent bonding with pro clima TESCO No.1, TESCO VANA or TESCO PROFIL adhesive tape or for ORCON F or ECO COLL joint adhesive.

Delivery Form:

Type	Mat. No.	EAN	Volume	Adhesive tape width	Covers	PU	PU/Pallet
can	11427	4026639114273	0.75 l	60 mm	approx. 60 m	6	84
				75 mm	approx. 45 m		
				150 mm	approx. 22 m		
can	11430	4026639114303	2.5 l	60 mm	approx. 185 m	4	40
				75 mm	approx. 150 m		
				150 mm	approx. 75 m		
dispenser bottle	11449	4026639114495	1 l	60 mm	approx. 75 m	6	60
				75 mm	approx. 60 m		
				150 mm	approx. 30 m		

Surfaces:

Before bonding, the substrate surface should be brushed clean with a broom or vacuum cleaned. Do not apply primer to frozen surfaces. The substrate material must be free from water-repellent substances (e.g. grease or silicone).

The primer can be used to treat all mineral substrates such as plaster or concrete. It can also be used to harden porous materials such as softwood fibre sub-roof panels, for example. In addition to this, it can be used to prepare (old) wood substrates for bonding.

If the tape is going to be used on a relatively dense, non-absorbent substrate (e.g. concrete), the primer first needs to dry thoroughly before the adhesive tape is applied.

Diffusion-permeable, absorbent substrates (e.g. softwood fibre sub-roof panels) may be slightly damp. The adhesive tape being used can be stuck straight on to the damp primer.

Usage notes:

Shake or stir the can well before use. One litre of primer can be used to treat an area of 4.5 m². To help you work even faster, you don't need to wait for the primer to dry on absorbent substrates, but can apply the adhesive straight to the damp primer.

Features/advantages:

- ✓ No drying required – adhesive can be applied straight to the damp primer on absorbent substrates
- ✓ Deep penetration
- ✓ Hardens the substrate
- ✓ Solvent-free
- ✓ Can be used with any pro clima adhesive tape

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommendations given or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and UK:
Phone: +353 46 9432104
Fax: +353 46 9432435
info@ecologicalbuildingsystems.com

For Stockists contact
Ireland
T. 046 9432104
F. 046 9432435
UK
T. 05600 758025
F. 05600 758026

Ecological Building Systems Ltd.

info@ecologicalbuildingsystems.com
www.ecologicalbuildingsystems.com

