

# TESCON INVIS

Black multi-purpose adhesive tape

NEW



## Technical Data:

Characteristics	Value
material	special fleece made from PP
release paper	siliconized paper
temperature resistance	long term from -40°C to +90°C
application temperature	from -10°C
colour	black
UV stability and outdoor exposure	3 months
storage	cool and dry

## Applications:

### Outside:

Wind-proofing of wall lining membrane, including behind suspended façades using pro clima SOLITEX WA, as well as of sarking membrane and roof lining membrane. Wind-proof bonding of wood-based panels used as sarking boards. Airtight bonding of roof-mounted vapour check and refurbishment vapour check and airtightness membrane.

### Inside:

Airtight bonding of vapour check and airtightness membrane as well as airtight wood-based panels.

All bonding, indoor and outdoor, can be between the same material as well as with adjacent structural components with a smooth, non-mineral surface (e.g. pipe penetrations, roof windows).

## Delivery Form:

Mat. No.	EAN	Length	Width	PU	PU/Pallet
11948	4026639119483	30 m	6 cm	10	48
11949	4026639119490	30 m	6 cm	20	Big pack * 24

\* only available by the box!

## Surfaces:

Before bonding, the substrate surface should be swept clean with a broom or wiped with a cloth. Bonding to frozen surfaces is not possible. The substrate material must be free of water-repellent substances (e.g. grease or silicone). The substrate must offer sufficient load-bearing capacity.

A permanent bond is achieved on all pro clima indoor and outdoor membranes (vapour check and airtightness membrane as well as trickle protection membrane and sarking membrane or wall lining membrane) and PE, PA, PP, aluminium foil used to create an airtight seal. Bonding and joints are possible with planed and painted wood, high density plastic and metal (e.g. pipes, windows etc.), hardboard (chipboard, OSB and veneer plywood, MDF board and softwood fibre sub-roof panels). Softwood fibre sub-roof panels require pre-treatment with TESCOON PRIMER RP before bonding. The best results for the safety of the structure can be achieved on high-quality substrates. The applicator is responsible for checking the suitability of the substrate. Adhesion tests are recommended.

## Features/advantages:

- ✓ For creating invisible bonds and joints behind suspended façades
- ✓ Very soft to the touch
- ✓ Waterproof
- ✓ Weather resistant for 3 months
- ✓ Very heat resistant

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommendations given or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and UK:  
Phone: +353 46 9432104  
Fax: +353 46 9432435  
info@ecologicalbuildingsystems.com

For Stockists contact  
Ireland  
T. 046 9432104  
F. 046 9432435  
UK  
T. 05600 758025  
F. 05600 758026

Ecological Building Systems Ltd.

info@ecologicalbuildingsystems.com  
www.ecologicalbuildingsystems.com

