



iab
Bord Agrément na hÉireann
Irish Agrément Board

Technical Data:

Characteristics	Value
material	special paper with reinforcement layer
release paper	siliconized paper
temperature resistance	long term from -40°C to +90°C
application temperature	from -10°C
colour	light blue
storage	cool and dry

Applications:

UNI TAPE is used to bond overlaps between vapour check and airtightness membrane securely, air tightly and permanently as well as for indoor joints between such membranes. Also suitable for bonding butt joints between wood-based panels. The bonds meet the requirements of DIN 4108-7, SIA 180 and ÖNorm B8110-2.

Delivery Form:

Mat. No.	EAN	Length	Width	PU	PU/Pallet
10655	4026639016539	30 m	6 cm	10	48
10687	4026639016546	30 m	6 cm	20	Big pack * 24
10110	4026639016331	30 m	4 cm	14	56

* only available by the box!

Surfaces:

Before bonding, the substrate surface should be swept clean with a broom or wiped with a cloth. Bonding to frozen surfaces is not possible. The substrate material must be free of water-repellent substances (e.g. grease or silicone). The substrate must offer sufficient load-bearing capacity. A permanent bond is achieved on all pro clima indoor membranes (vapour check and airtightness membrane as well as trickle protection membrane) and PE, PA, PP and aluminium foil used to create an airtight seal. Bonding and joints are possible with planed and painted wood, high density plastic and metal (e.g. pipes, windows etc.), hardboard (chipboard, OSB and veneer plywood). The best results for the safety of the structure can be achieved on high-quality substrates. The applicator is responsible for checking the suitability of the substrate. Adhesion tests are recommended. UNI TAPE 4 cm can only be used to for bonds on hard substrates (e.g. when laying on rafters lengthwise).

Features/advantages:

- ✓ Easy to tear off by hand
- ✓ High initial bond strength
- ✓ Waterproof adhesive
- ✓ Low-emission

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommendations given or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and UK:
Phone: +353 46 9432104
Fax: +353 46 9432435
info@ecologicalbuildingsystems.com

For Stockists contact
Ireland
T. 046 9432104
F. 046 9432435
UK
T. 05600 758025
F. 05600 758026

Ecological Building Systems Ltd.

info@ecologicalbuildingsystems.com
www.ecologicalbuildingsystems.com

